DATASHEET

The small radiolucent Ambu WhiteSensor 40554 has been specially developed for babies and newborns.


The electrode features a skin-friendly solid gel and breathable cloth backing material.

Key benefits

- Skin-friendly solid gel supports the quality of the signal
- Soft cloth backing allows the skin to breathe
- Small size is suitable for neonatal patients
- Radiolucency allows the electrode to remain on the patient during X-ray procedures
- Prewired with 1,5 mm connector
- Lead wire length is 60 cm

Ambu® WhiteSensor 40554

ECG Electrode Single use









Solid gel

Cloth backing

Silver sensor



Radiolucent

Breathable backing



WhiteSensor

SPECIFICATIONS

Dimensions

Dimensions		
Electrode size (length x width in mm)	22 x 22	
Skin contact size (length x width in mm)	22 x 22	
Skin contact area (in mm²)	484	
Sensor		
Sensor material	Silver/silver chloride (Ag/AgCl)	
Gel system	Solid gel	
Gel area (in mm²)	484	
Electrical data (ANSI/AAMI)		
AC impedance - typical	220 Ω	
DC offset potential - typical	3.5 mV	
Defibrillation overload recovery - typical	12.65 mV	
Rate of change for polarisation potential - typical	-0.26 mV/s	
Combined offset instability and internal noise	0.3 µV	
Bias current tolerance	4.5 mV	

Environment				
Electrode is not made with natural rubber latex				
Wire is not made with natural rubber latex				
Packaging is PVC-free				
X-ray & MRI				
Radiolucent	Yes			
MR Conditional	No			
Shelf life				
Unopened pouch*	24 months			

*from date of production



K = 1.5 mm connector

MATERIALS

Electrode	
Bio-compatible	Yes
Backing material	Non-woven (Cloth)
Supporting label	Printed Polyethylene (PE) foam
Lead wire core	Carbon
Lead wire insulation	Polyvinyl chloride (PVC)
Release liner	Siliconised polyester
Packaging	
Pouch (outer/middle/inner layers)	Polyester/Aluminium/Polyethylene
Boxes	Cardboard
Options	
Pre-wired connectors	K
Lead wire colors	Red, yellow, black
Precaution	
Single use only	

AVAILABLE CONFIGURATIONS*

Reference number	Units/liner	Units/pouch	Units/inner box	Units/outer box
40554	3	3	300	3000
			6	

*some configurations may not be available worldwide



Ambu Limited

Incubator 2, Alconbury Weald Enterprise Campus, Cambridgeshire, PE28 4XA T 01480 498 403 ambu.co.uk

