

DATASHEET

The single-use concept of aScope 4 Broncho once and for all solves the problem of accessibility, simplifies set-up for procedures, eliminates the need for complex cleaning procedures and minimizes the risk of cross-contamination. It comes sterile straight from the pack, offering improved patient safety and workflow.

The aScope 4 Broncho Slim offers high quality bronchoscopy for a broad range of procedures. When connected to Ambu aView™ 2 Advance, aScope 4 Broncho Slim gives you clear visibility of the near and distal bronchial segments. The clear, sharp images and adaptive light control make identification of lung anatomy and navigation in the bronchial tree easy.

The high bending angles and precise tip motion of aScope 4 Broncho Slim allows you to easily navigate into all segments of the lung. The high quality handle is designed with a shaped, rippled surface to provide a comfortable grip throughout the procedure. The lightweight and ergonomic design makes aScope 4 Broncho Slim easy to use.

The aScope 4 Broncho Slim has a small outer diameter of 3.8 mm. It is the ideal solution for a wide range of bronchoscopy procedures: from intubation to the placement and control of double lumen tubes and bronchial blockers in the OR. The ultra slim design makes the aScope 4 Broncho Slim ideal for placing an ET tube ≥ 5 mm or a DLT \geq size 35 Fr.

Ambu® aScope™ 4 Broncho Slim 3.8/1.2

Guaranteed sterility, ready when you are



KEY BENEFITS

Instant availability

No risk of cross-contamination

Cost effective

High degree of usability

Clear, sharp images

Smooth and easy navigation

World's first single-use bronchoscope with bioplastic handle

SPECIFICATIONS

Optical system

Field of View	85°
Direction of View	0° (forward viewing)
Depth of Field	6 - 50 mm
Illumination method	2 LEDs

Insertion portion

Bending section	180° up, 180° down
Insertion cord diameter	3.8 mm (0.15")
Distal tip diameter	4.2 mm (0.16")
Maximum diameter of insertion portion	4.3 mm (0.17")
Minimum endotracheal tube size (inner diameter)	5.0 mm
Minimum double lumen tube size (inner diameter)	35 Fr
Working length	600 mm (23.6")

Channel

Average inner diameter	1.2 mm (0.047")
Minimum instrument channel width	1.2 mm (0.047")

Suction connector

Connecting tube inner diameter range	6.5 mm - 9.5 mm
--------------------------------------	-----------------

Storage

Temperature**	10 - 25 °C (50 to 77 °F)
Relative humidity	10 - 85 %
Atmospheric pressure	50 - 106 kPa

Transportation

Temperature	-10 - 55 °C (14 to 131 °F)
Relative humidity	10 - 95 %
Atmospheric pressure	50 - 106 kPa

Operating environment

Temperature	10 - 40 °C (50 to 104 °F)
Relative humidity	30 - 85 %
Atmospheric pressure	80 - 106 kPa
Altitude	≤ 2000 m

Sterilisation

Method of sterilisation	ETO
-------------------------	-----

Sustainability

Handle material	Bio-attributed ABS plastic
-----------------	----------------------------

ORDERING SPECIFICATIONS

Item no.	Quantity/box	Transportation quantity
476001000	5	20

* There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination.

** Storage under higher temperatures may impact shelf life.



Learn more about Ambu's sustainability initiatives:
<https://www.ambu.com/endoscopy/single-use-endoscopy/environment>

Ambu FOREVER FORWARD

Ambu Ltd
 Incubator 2
 Alconbury Weald
 Enterprise Campus
 Alconbury Weald
 Cambridgeshire
 PE28 4XA
 Tel 01480 498403
www.ambu.co.uk



Ambu aScope 4 Broncho Slim and Ambu aView 2 Advance Next Gen



Ergonomic and lightweight handle designed to give you a firm and comfortable grip